

PAPEL ESTUCADO BRILLO 1 CARA

FICHA TÉCNICA: UPM FLEXPACK™

Looking for a great price-quality ratio for your packaging? One side coated papers have a bright, clear and smooth printing surface. It's your choice when you need reliable and consistent performance in various converting applications.

Category	Packaging papers
Grade	One side coated (C1S)
End use	Biscuits and other food wrapping areas PP/PE coating and laminating base Soup pouches
Furnish	Northern softwood kraft pulp
Printing method	Digital reel fed printing Flexo Letterpress Offset Thermal transfer UV-inkjet
Format/Size	Reels
Reel Diameter (cm)	75,0 - 150,0
Reel Width (cm)	50,0 - 250,0
Core (mm)	71,0 / 76,0 / 153,0
Wrapping	Strong kraft paper Strong moisture proof polyethylene laminated kraft paper
Certificates and labels	94/62 EC Heavy Metal Certificate BfR Food Certificate EMAS EN 71/3:1988 D Safety of Toys FDA Food Certificate Food Approval Statement FSC Chain-of-Custody ISO 14001 ISO 22000 ISO 9001 PEFC Chain-of-Custody
Note	FSC and PEFC on request but subject to availability.

TECHNICAL TARGET VALUES:

Basis Weight (ISO 536) (g/m²)	45.0	50.0	60.0	70.0	80.0	90.0
CIE Whiteness (ISO 11475:2017) (%)	118.0	118.0	118.0	120.0	120.0	120.0
Gloss Hunter (ISO 8254-1) (%)	62.0	64.0	66.0	66.0	66.0	66.0
Roughness PPS10 TS (µm)	1.0	0.9	0.9	0.9	0.9	0.9
Thickness (ISO 534) (µm)	42.0	45.0	52.0	60.0	69.0	80.0
Tensile Strength MD (kN/m)	3.5	4.0	4.5	5.5	6.5	7.0
Tensile Strength CD (kN/m)	1.6	2.0	2.2	2.5	3.0	3.3

Please note: Technical values are informative and subject to production variations.